ASRock Riferimento tecnico - D&R

Come abilitare la funzione Wake on LAN in stato S5 in Windows 10? D: 1.

R: Segui i passaggi seguenti per soddisfare la tua richiesta

Passaggio 1: deseleziona l'opzione di avvio rapido nel Pannello di controllo.

| 🗑 System Settings | | | × |
|---|-----|----------------------|---|
| ← → → ↑ 🗃 > Control Panel > Hardware and Sound > Power Options > System Settings | ڻ × | Search Control Panel | Q |
| Define power buttons and turn on password protection Choose the power settings that you want for your computer. The changes you make to the settings on this page apply to all of your power plans. Power and sleep button settings When I press the power button: Shut down When I press the sleep button: Shut down Shutdown settings I urn on fast startup (recommended) This helps start your PC faster after shutdown. Restart isn't affected. Learn More Show in Power menu. Jok Show in account picture menu. | | | |
| Save changes Cancel | | | |

Passaggio 2: decomprimi il file EnableWOLInFastStartup e poi clicca con il pulsante destro del mouse su Esegui come amministratore sul file WakeOnFastStartup.bat per installarlo.

| 1 |] 🗖 = 1 | | | Application Tools | EnableWOLInFastStartup | |
|------|---------|-------|------|-------------------|------------------------|--|
| File | Home | Share | View | Manage | | |

Link: https://www.asrock.com/support/download/EnableWOLInFastStartup.zip

X 0 ableWOLInFastStart... 🔎 Name Date modified Туре Size 🖈 Quick access EnableWOLInFastStartup 11/7/2014 1:59 AM PDF File 72 KB Desktop * ReadMe-WakeOnFastStartup 10/30/2014 6:09 AM Text Document 1 KB Downloads WakeOnFastStart 10/30/2014 5-34 AM, Windows Batch File 10 KB Documents 4 Open Pictures Edit 📙 EnableWOLInFas 🖈 Print 🌍 Run as administrator) Music Scan with Windows Defender.. Videos 🖻 Share C OneDrive Give access to > This PC Restore previous versions BUNTU 16_1 (D:) Send to > Cut Petwork Сору Create shortcut Delete Rename Properties 100 E 3 items 1 item selected 9.33 KB

Pagina 1

TSD-QA (2018/03)

TSD-QA (2018/03)

Passaggio 3: controlla l'opzione di avvio rapido nel Pannello di controllo.

| law System Settings | | . 🗆 | × |
|---|--------------------|-----|---|
| ← → v ↑ 🍃 > Control Panel > Hardware and Sound > Power Options > System Settings v ð | Search Control Par | nel | م |
| Define power buttons and turn on password protection | | | |
| Choose the power settings that you want for your computer. The changes you make to the settings on this page apply to all of your power plans. | | | |
| Power and sleep button settings | | | |
| 🔘 When I press the power button: Shut down 🗸 | | | |
| When I press the sleep button: | | | |
| Shutdown settings | | | |
| Turn on fast startup (recommended) This helps start your PC faster after shutdown. Restart isn't affected. <u>Learn More</u> | | | |
| Hibernate Show in Power menu. | | | |
| ✓ Lock Show in account picture menu. | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| Save changes Cancel | | | |

Dopodiché, Wake on LAN verrà abilitato in stato S5.

2. D: Come regolo la memoria condivisa mentre utilizzo la CPU Raven Ridge sulla piattaforma AM4?

- R: Se desideri regolare la memoria condivisa, procedi nel seguente modo per trovare e regolare le impostazioni di OC.
 - 1. Premi "F2" o "Canc" durante il POST per accedere alla configurazione del BIOS
 - 2. Fare riferimento al seguente percorso per regolare le impostazioni di OC.
 - a. Advanced\AMD CBS\NBIO Common Options\GFX Config IGC :Forces
 - b. Advanced\AMD CBS\NBIO Common Options\UMA Mode : UMA_Spec
 - c. Advanced\AMD CBS\NBIO Common Options\UMA Frame Buffer Size: Scegli una dimensione preferita

| /ISRock LIEFI | | | | | | | | | |
|---|----------------------|------------------------------|--|--|--|--|--|--|--|
| 🌐 Main 🍈 OC Tweaker 🛛 🗚 Advanced | X Tool O H/W Monitor | Security O Boot Exit | | | | | | | |
| Advanced\AMD CBS\NBIO Common Options\GFX Configurat | tion | | | | | | | | |
| I Integrated Graphics Controller | Forces | | | | | | | | |
| I UMA Mode | UMA_SPECIFIED | Description | | | | | | | |
| 1 UMA Version | Auto | Set UMA FB size | | | | | | | |
| I UMA Frame buffer Size | 1G | | | | | | | | |
| | NULU | | | | | | | | |
| | | Get details via OR code | | | | | | | |
| 1 | Eng]: | ish Tue 03/20/2018, 17:20:24 | | | | | | | |

Pagina 3

TSD-QA (2018/03)

d. OC Tweaker\OC Mode Change Switch\AMD CBS Setting



3. Dopo aver regolato le opzioni qui sopra, premi "F10" per salvare la configurazione

3. D: Quando utilizzo la scheda VGA con CPU AM4 grafica integrata, il driver dell'adattatore dello schermo

integrato mostra un punto esclamativo, cosa devo fare?

R: Se utilizzi la scheda VGA e l'adattatore integrato mostra un punto esclamativo come nell'immagine in basso, attieniti alla procedura per rimuovere il punto esclamativo.

🗄 Device Manager File Action View Help ? 🖬 晃 34 DESKTOP-APQFOEE > 4 Audio inputs and outputs Computer Disk drives 🔜 Display adapters 🙀 AMD Radeon(TM) RX Vega 11 Graphics 🏣 Radeon RX 570 Series 🎽 Firmware 🛺 Human Interface Devices > IDE ATA /ATA DI

- 1. Premi "F2" o "Canc" durante il POST per accedere alla configurazione del BIOS
- 2. Scegli l'adattatore video principale come scheda grafica

Percorso: Advanced\AMD PBS\Primary Video Adapter\Int Graphics (IGD)



3. Dopo aver regolato le opzioni sopra, premi "F10" per salvare la configurazione.

Puoi provare anche il metodo di seguito.

- 1. Premi "F2" o "Canc" durante il POST per accedere alla configurazione del BIOS
- 2. Disattiva CSM

Percorso: Boot/CSM/Disable

| | /ISRock LIEFI | | | | | | | | | | |
|-------|---------------|-----------------------|----------|----------|-----|-------------|--------|--|---------------------------------|----------------------------|-----|
| | i Main | 🙃 OC Tweaker | Advanced | × 1001 | C | H/W Monitor | 💌 Secu | rity | 😃 Boot | Ex1 | t |
| | Boot\CSM(Con | npatibility Support M | odule) | | | | | | | | |
| I CSM | | | | | | Disabled | | | | | |
| | | | | | | | | Desci | ription | | |
| | | | E | | | | | Enable to launch the Compatibility Support Module. If you are using | | | |
| | | | | - | CSM | × | | Windows devices | 8 64-bit UEFI a support UEFI, y | nd all of y ou may also | our |
| | | | | Disabled | Ð | | | disable | CSM for faster | boot speed. | |
| | | | | Lildbieu | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | / | Get deta | ails via OR code | | |
| | | | | | | | V | | | | |
| | | | | | | | glish | ١ | lon 02/12/2018. | 00:00:47 | |

3. Dopo aver regolato le opzioni sopra, premi "F10" per salvare la configurazione.

TSD-QA (2018/03)